

Product information

Value PAR16 50 36° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	350 lm / 850 cd	
Nominal System Power	4,3 W	
Rated System Power	4,3 W	
Voltage	220-240 V	
Luminous efficiency	87,5 lm/W	
Colour temperature	3000 K	
Dimmable	non-dim	
Beam angle	36°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	5 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 50 non-dim 36° 4,3W/830 GU10	4058075096622	4058075096639

Product information

Value PAR16 50 36° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	350 lm / 850 cd	
Nominal System Power	4,3 W	
Rated System Power	4,3 W	
Voltage	220-240 V	
Luminous efficiency	87,5 lm/W	
Colour temperature	4000 K	
Dimmable	non-dim	
Beam angle	36°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	5 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 50 non-dim 36° 4,3W/840 GU10	4058075055155	4058075055162

Product information

Value PAR16 50 36° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	350 lm / 850 cd	
Nominal System Power	4,3 W	
Rated System Power	4,3 W	
Voltage	220-240 V	
Luminous efficiency	87,5 lm/W	
Colour temperature	6500 K	
Dimmable	non-dim	
Beam angle	36°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	5 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 50 non-dim 36° 4,3W/865 GU10	4058075817715	4058075817722

Product information

Value PAR16 80 36° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	575 lm / 180 cd	
Nominal System Power	6,9 W	
Rated System Power	6,9 W	
Voltage	220-240 V	
Luminous efficiency	95,83 lm/W	
Colour temperature	3000 K	
Dimmable	non-dim	
Beam angle	36°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 80 non-dim 36° 6,9W/830 GU10	4058075096646	4058075096653

Product information

Value PAR16 80 36° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data

Luminous flux / Candela	575 lm / 1439 cd
Nominal System Power	6,9 W
Rated System Power	6,9 W
Voltage	220-240 V
Luminous efficiency	95,83 lm/W
Colour temperature	4000 K
Dimmable	non-dim
Beam angle	36°
CRI	80
Dimensions (D/L)	51 / 55 mm
Energy class	A+
Energy consumption	7 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 80 non-dim 36° 6,9W/840 GU10	4058075096660	4058075096677

Product information

Value PAR16 80 36° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	575 lm / 180 cd	
Nominal System Power	6,9 W	
Rated System Power	6,9 W	
Voltage	220-240 V	
Luminous efficiency	95,83 lm/W	
Colour temperature	6500 K	
Dimmable	non-dim	
Beam angle	36°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 80 non-dim 36° 6,9W/865 GU10	4058075096684	4058075096691

Product information

Value PAR16 80 60° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	575 lm / 180 cd	
Nominal System Power	6,9 W	
Rated System Power	6,9 W	
Voltage	220-240 V	
Luminous efficiency	95,83 lm/W	
Colour temperature	3000 K	
Dimmable	non-dim	
Beam angle	60°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 80 non-dim 60° 6,9W/830 GU10	4058075096769	4058075096776

Product information

Value PAR16 80 60° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	575 lm / 180 cd	
Nominal System Power	6,9 W	
Rated System Power	6,9 W	
Voltage	220-240 V	
Luminous efficiency	95,83 lm/W	
Colour temperature	4000 K	
Dimmable	non-dim	
Beam angle	60°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 80 non-dim 60° 6,9W/840 GU10	4058075096783	4058075096790

Product information

Value PAR16 80 120° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	575 lm / 180 cd	
Nominal System Power	6,9 W	
Rated System Power	6,9 W	
Voltage	220-240 V	
Luminous efficiency	95,83 lm/W	
Colour temperature	3000 K	
Dimmable	non-dim	
Beam angle	120°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 80 non-dim 120° 6,9W/830 GU10	4058075096707	4058075096714

Product information

Value PAR16 80 120° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	575 lm / 180 cd	
Nominal System Power	6,9 W	
Rated System Power	6,9 W	
Voltage	220-240 V	
Luminous efficiency	95,83 lm/W	
Colour temperature	4000 K	
Dimmable	non-dim	
Beam angle	120°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 80 non-dim 120° 6,9W/840 GU10	4058075096721	4058075096738

Product information

Value PAR16 80 120° non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of halogen lamps due to compact full glass design and single optic
- Instant 100 % light, no warm-up time
- Ideal for economical spotlighting

Areas of application

- Shops
- Hospitality
- Museums, art galleries
- Residential interiors
- As a downlight for marking walkways, doors, stairs, etc.
- Spotlighting for accents
- Display cabinets and shop windows
- Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor applications only in suitable luminaires

Product features

- Professional LED alternative to high voltage halogen lamps
- Mercury-free lamps
- Made in Germany

Most important technical data		
Luminous flux / Candela	575 lm / 180 cd	
Nominal System Power	6,9 W	
Rated System Power	6,9 W	
Voltage	220-240 V	
Luminous efficiency	95,83 lm/W	
Colour temperature	6500 K	
Dimmable	non-dim	
Beam angle	120°	
CRI	80	
Dimensions (D/L)	51 / 55 mm	
Energy class	A+	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE PAR16 80 non-dim 120° 6,9W/865 GU10	4058075096745	4058075096752

Product information

Value CL A FIL 40 non-dimmable



Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	470 lm / n.n. cd	
Nominal System Power	4 W	
Rated System Power	4 W	
Voltage	220-240 V	
Luminous efficiency	117,5 lm/W	
Colour temperature	2700 K	
Dimmable	non-dim	
Beam angle	300°	
CRI	80	
Dimensions (D/L)	60 / 105 mm	
Energy class	A++	
Energy consumption	4 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FIL 40 non-dim 4W/827 E27	4058075819634	4058075819641

Product information

Value CL A FIL 40 non-dimmable



Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	470 lm / n.n. cd	
Nominal System Power	4 W	
Rated System Power	4 W	
Voltage	220-240 V	
Luminous efficiency	117,5 lm/W	
Colour temperature	4000 K	
Dimmable	non-dim	
Beam angle	300°	
CRI	80	
Dimensions (D/L)	60 / 105 mm	
Energy class	A++	
Energy consumption	4 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FIL 40 non-dim 4W/840 E27	4058075153523	4058075153530

Product information

Value CL A FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	5 W
Rated System Power	5 W
Voltage	220-240 V
Luminous efficiency	94 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 112 mm
Energy class	A+
Energy consumption	5 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 40 non-dim 5W/827 E27	4052899326927	4052899326934

Product information

Value CL A FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	5 W
Rated System Power	5 W
Voltage	220-240 V
Luminous efficiency	94 lm/W
Colour temperature	4000 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 112 mm
Energy class	A+
Energy consumption	5 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 40 non-dim 5W/840 E27	4058075127081	4058075127098

Product information

Value CL A FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	5,5 W
Rated System Power	5,5 W
Voltage	220-240 V
Luminous efficiency	94 lm/W
Colour temperature	6500 K
Dimmable	non-dim
Beam angle	200°
CRI	80
Dimensions (D/L)	60 / 112 mm
Energy class	A+
Energy consumption	6 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 40 non-dim 5,5W/865 E27	4052899971011	4052899971103

Product information

Value CL A FIL 60 non-dimmable



Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	806 lm / n.n. cd	
Nominal System Power	7 W	
Rated System Power	7 W	
Voltage	220-240 V	
Luminous efficiency	115,14 lm/W	
Colour temperature	2700 K	
Dimmable	non-dim	
Beam angle	300°	
CRI	80	
Dimensions (D/L)	60 / 105 mm	
Energy class	A++	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FIL 60 non-dim 7W/827 E27	4058075819658	4058075819665

Product information

Value CL A FIL 60 non-dimmable



Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	806 lm / n.n. cd	
Nominal System Power	7 W	
Rated System Power	7 W	
Voltage	220-240 V	
Luminous efficiency	115,14 lm/W	
Colour temperature	4000 K	
Dimmable	non-dim	
Beam angle	300°	
CRI	80	
Dimensions (D/L)	60 / 105 mm	
Energy class	A++	
Energy consumption	7 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FIL 60 non-dim 7W/840 E27	4058075153547	4058075153554

Product information

Value CL A FR 60 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	806 lm / n.n. cd
Nominal System Power	8,5 W
Rated System Power	8,5 W
Voltage	220-240 V
Luminous efficiency	100,75 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 112 mm
Energy class	A+
Energy consumption	9 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 60 non-dim 8,5W/827 E27	4052899326842	4052899326859

Product information

Value CL A FR 60 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	806 lm / n.n. cd
Nominal System Power	8,5 W
Rated System Power	8,5 W
Voltage	220-240 V
Luminous efficiency	100,75 lm/W
Colour temperature	4000 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 112 mm
Energy class	A+
Energy consumption	9 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 60 non-dim 8,5W/840 E27	4052899973381	4052899973398

Product information

Value CL A FR 60 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	806 lm / n.n. cd
Nominal System Power	8,5 W
Rated System Power	8,5 W
Voltage	220-240 V
Luminous efficiency	100,75 lm/W
Colour temperature	6500 K
Dimmable	non-dim
Beam angle	200°
CRI	80
Dimensions (D/L)	60 / 112 mm
Energy class	A+
Energy consumption	9 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 60 non-dim 8,5W/865 E27	4052899326873	4052899326880

Product information

Value CL A FIL 75 non-dimmable



Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	1055 lm / n.n. cd	
Nominal System Power	8 W	
Rated System Power	8 W	
Voltage	220-240 V	
Luminous efficiency	13,13 lm/W	
Colour temperature	2700 K	
Dimmable	non-dim	
Beam angle	320°	
CRI	80	
Dimensions (D/L)	60 / 105 mm	
Energy class	A++	
Energy consumption	8 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FIL 75 non-dim 8W/827 E27	4058075153561	4058075153578

Product information

Value CL A FIL 75 non-dimmable



Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	1055 lm / n.n. cd	
Nominal System Power	8 W	
Rated System Power	8 W	
Voltage	220-240 V	
Luminous efficiency	13,13 lm/W	
Colour temperature	4000 K	
Dimmable	non-dim	
Beam angle	320°	
CRI	80	
Dimensions (D/L)	60 / 105 mm	
Energy class	A++	
Energy consumption	8 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FIL 75 non-dim 8W/840 E27	4058075153585	4058075153592

Product information

Value CL A FR 75 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	1060 lm / n.n. cd
Nominal System Power	10 W
Rated System Power	10 W
Voltage	220-240 V
Luminous efficiency	106 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 115 mm
Energy class	A+
Energy consumption	10 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 75 non-dim 10W/827 E27	4052899971028	4052899971110

Product information

Value CL A FR 75 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	1060 lm / n.n. cd
Nominal System Power	10 W
Rated System Power	10 W
Voltage	220-240 V
Luminous efficiency	106 lm/W
Colour temperature	4000 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 115 mm
Energy class	A+
Energy consumption	10 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 75 non-dim 10W/840 E27	4052899973404	4052899973411

Product information

Value CL A FR 75 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	1080 lm / n.n. cd
Nominal System Power	10 W
Rated System Power	10 W
Voltage	220-240 V
Luminous efficiency	108 lm/W
Colour temperature	6500 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 115 mm
Energy class	A+
Energy consumption	10 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 75 non-dim 10W/865 E27	4052899971035	4052899971127

Product information

Value CL A FIL 100 non-dimmable



Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	1521 lm / n.n. cd
Nominal System Power	11 W
Rated System Power	11 W
Voltage	220-240 V
Luminous efficiency	152 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	300°
CRI	80
Dimensions (D/L)	60 / 105 mm
Energy class	A++
Energy consumption	11 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FIL 100 non-dim 11W/827 E27	4058075153608	4058075153615

Product information

Value CL A FIL 100 non-dimmable



Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	1521 lm / n.n. cd
Nominal System Power	11 W
Rated System Power	11 W
Voltage	220-240 V
Luminous efficiency	152 lm/W
Colour temperature	4000 K
Dimmable	non-dim
Beam angle	300°
CRI	80
Dimensions (D/L)	60 / 105 mm
Energy class	A++
Energy consumption	11 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FIL 100 non-dim 11W/840 E27	4058075153622	4058075153639

Product information

Value CL A FR 100 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	1521 lm / n.n. cd
Nominal System Power	13 W
Rated System Power	13 W
Voltage	220-240 V
Luminous efficiency	152 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 115 mm
Energy class	A+
Energy consumption	13 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 100 non-dim 13W/827 E27	4052899971097	4052899971189

Product information

Value CL A FR 100 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	250 lm / n.n. cd
Nominal System Power	3,2 W
Rated System Power	3,2 W
Voltage	220-240 V
Luminous efficiency	83,33 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	35 / 106 mm
Energy class	A+
Energy consumption	4 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 100 non-dim 13W/840 E27	4052899973428	4052899973435

Product information

Value CL A FR 100 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	1521 lm / n.n. cd
Nominal System Power	13 W
Rated System Power	13 W
Voltage	220-240 V
Luminous efficiency	152 lm/W
Colour temperature	6500 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	60 / 115 mm
Energy class	A+
Energy consumption	13 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL A FR 100 non-dim 13W/865 E27	4052899971042	4052899971134

Product information

Value CL B FIL 40 non-dimmable



Product benefits

- Clear lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- Not dimmable

Most important technical data		
Luminous flux / Candela	470 lm / n.n. cd	
Nominal System Power	4 W	
Rated System Power	4 W	
Voltage	220-240 V	
Luminous efficiency	117,5 lm/W	
Colour temperature	2700 K	
Dimmable	non-dim	
Beam angle	300°	
CRI	80	
Dimensions (D/L)	35 / 97 mm	
Energy class	A++	
Energy consumption	4 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL B FIL 40 non-dim 4W/827 E14	4058075819672	4058075819689

Product information

Value CL B FIL 40 non-dimmable



Product benefits

- Clear lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- Not dimmable

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	4 W
Rated System Power	4 W
Voltage	220-240 V
Luminous efficiency	117,5 lm/W
Colour temperature	4000 K
Dimmable	non-dim
Beam angle	300°
CRI	80
Dimensions (D/L)	35 / 97 mm
Energy class	A++
Energy consumption	4 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL B FIL 40 non-dim 4W/840 E14	4058075114678	4058075114685

Product information

Value CL B FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Chandeliers
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	5,7 W
Rated System Power	5,7 W
Voltage	220-240 V
Luminous efficiency	94 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	35 / 106 mm
Energy class	A+
Energy consumption	6 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL B FR 40 non-dim 5,7W/827 E14	4052899326453	4052899326460

Product information

Value CL B FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Chandeliers
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	470 lm / n.n. cd	
Nominal System Power	5,7 W	
Rated System Power	5,7 W	
Voltage	220-240 V	
Luminous efficiency	94 lm/W	
Colour temperature	4000 K	
Dimmable	non-dim	
Beam angle	180°	
CRI	80	
Dimensions (D/L)	35 / 106 mm	
Energy class	A+	
Energy consumption	6 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL B FR 40 non-dim 5,7W/840 E14	4052899973367	4052899973374

Product information

Value CL B FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Chandeliers
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	5,7 W
Rated System Power	5,7 W
Voltage	220-240 V
Luminous efficiency	94 lm/W
Colour temperature	6500 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	35 / 106 mm
Energy class	A+
Energy consumption	6 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL B FR 40 non-dim 5,7W/865 E14	4052899971066	4052899971158

Product information

Value CL B FR 60 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Chandeliers
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	806 lm / n.n. cd
Nominal System Power	7 W
Rated System Power	7 W
Voltage	220-240 V
Luminous efficiency	115,14 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	38 / 110 mm
Energy class	A+
Energy consumption	7 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL B FR 60 non-dim 7W/827 E14	4058075152915	4058075152922

Product information

Value CL P FIL 40 non-dimmable



Product benefits

- Clear lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	470 lm / n.n. cd	
Nominal System Power	4 W	
Rated System Power	4 W	
Voltage	220-240 V	
Luminous efficiency	117,5 lm/W	
Colour temperature	2700 K	
Dimmable	non-dim	
Beam angle	300°	
CRI	80	
Dimensions (D/L)	45 / 78 mm	
Energy class	A++	
Energy consumption	4 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL P FIL 40 non-dim 4W/827 E14	4058075819696	4058075819702

Product information

Value CL P FIL 40 non-dimmable



Product benefits

- Clear lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product features

- Professional LED lamps for line voltage
- Not dimmable
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	470 lm / n.n. cd	
Nominal System Power	4 W	
Rated System Power	4 W	
Voltage	220-240 V	
Luminous efficiency	117,5 lm/W	
Colour temperature	4000 K	
Dimmable	non-dim	
Beam angle	300°	
CRI	80	
Dimensions (D/L)	45 / 78 mm	
Energy class	A++	
Energy consumption	4 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	0 years	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL P FIL 40 non-dim 4W/840 E14	4058075112520	4058075112537

Product information

Value CL P FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Atmospheric accent lighting throughout the home
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	5,7 W
Rated System Power	5,7 W
Voltage	220-240 V
Luminous efficiency	94 lm/W
Colour temperature	2700 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	45 / 80 mm
Energy class	A+
Energy consumption	6 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL P FR 40 non-dim 5,7W/827 E14	4058075147898	4058075147904

Product information

Value CL P FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Atmospheric accent lighting throughout the home
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	5,7 W
Rated System Power	5,7 W
Voltage	220-240 V
Luminous efficiency	94 lm/W
Colour temperature	4000 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	45 / 80 mm
Energy class	A+
Energy consumption	6 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL P FR 40 non-dim 5,7W/840 E14	4058075147911	4058075147928

Product information

Value CL P FR 40 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Atmospheric accent lighting throughout the home
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data

Luminous flux / Candela	470 lm / n.n. cd
Nominal System Power	5,7 W
Rated System Power	5,7 W
Voltage	220-240 V
Luminous efficiency	94 lm/W
Colour temperature	6500 K
Dimmable	non-dim
Beam angle	180°
CRI	80
Dimensions (D/L)	45 / 80 mm
Energy class	A+
Energy consumption	6 kWh/1000 h
Lifetime (L70/B50)	10000 h
Guarantee	0 years
Packaging	FC

Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL P FR 40 non-dim 5,7W/865 E14	4058075127630	4058075127647

Product information

Value CL P FR 60 non-dimmable



Product benefits

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Areas of application

- Domestic applications
- General illumination
- Atmospheric accent lighting throughout the home
- Outdoor applications only in suitable luminaires

Product features

- LED alternative to conventional lamps
- Mercury-free lamps

Most important technical data		
Luminous flux / Candela	806 lm / n.n. cd	
Nominal System Power	8 W	
Rated System Power	8 W	
Voltage	220-240 V	
Luminous efficiency	100,75 lm/W	
Colour temperature	2700 K	
Dimmable	non-dim	
Beam angle	150°	
CRI	80	
Dimensions (D/L)	45 / 90 mm	
Energy class	A+	
Energy consumption	8 kWh/1000 h	
Lifetime (L70/B50)	10000 h	
Guarantee	S	
Packaging	FC	
Product	EAN10	EAN40 (ship.unit 10)
LED VALUE CL P FR 60 non-dim 8W/827 E14	4058075152939	4058075152946